

tralift™ Range of manual chain hoists

• COMPREHENSIVE RANGE

- WLL 0.25 to 20 tonnes.
 - Swivel 360° hooks.
 - Automatic double pawl brake (except 250 kg)
 - Tested to 150% of working load limit.
 - Self-lubricating anti-corrosion chain.
- (Salt spray resistance > 400 hours, and at temperatures of up to 200°).
- Optional load limiting device.

Model	WLL	Number of falls	effort on hand chain (N)	Load chain (mm)	Hand chain (mm)	Hoist weight for 3 m lgt (kg)	Chain weight** extra per m (kg)
250	250 kg	1	340	4 x 12	2,4 x 14	4	0,54
500	500 kg	1	200	6 x 18	5 x 25	9,5	1,7
1000	1000 kg	1	320	6 x 18	5 x 24	11,5	1,7
1500	1500 kg	1	360	8 x 24	5 x 24	16,7	2,3
2000	2000 kg	2	328	6 x 18	5 x 24	14,6	3,4
2000	2000 kg	1	365	8 x 24	5 x 24	18,5	2,3
3000	3000 kg	2	385	8 x 24	5 x 24	21,2	3,7
5000	5000 kg	2	435	10 x 30	5 x 24	41,8	5,3
10 000	10.000 kg	4	435	10 x 30	5 x 24	81,7	9,7
20 000*	20 000 kg	8	435 x 2	10 x 30	5 x 24	173	19,4

* - model on request

** - Weight of load chain and hand chain per meter



Bravo™ RANGE OF LEVER HOISTS

• MULTI-PURPOSE, ROBUST, SAFE ...

- WLL 0.25 to 6 tonnes.
 - High-tensile alloy steel lever hoist. Ideal for building and civil engineering and industry.
 - Can be used in any position, both on building sites and in workshops.
 - Ideal for pulling, lifting, positioning, adjusting.
 - The hoist rotates freely round 360° on swivel hooks with overload opening indicators.
 - Selection of neutral position not possible once load taken up, with automatic engagement of the brake.
 - Automatic double pawl brake (except 250 kg)
 - Tested to 150% of working load limit.
 - Self-lubricating anti-corrosion chain.
- (Salt spray resistance > 400 hours, and at temperatures of up to 200°).
- Optional load limiting device.

Model	WLL	Number of strands	Standard lifting height* (m)	Maximum force on lever (N)	Weight (kg)	Chain size** (mm)
250	250 kg	1	1,5	340	2	4 x 12
500	500 kg	1	1,5	340	4	5 x 15
750	750 kg	1	1,5	140	7	6 x 18
1500	1500 kg	1	1,5	220	11	8 x 24
3000	3000 kg	1	1,5	320	21	10 x 30
6000	6000 kg	2	1,5	340	31	10 x 30

* - Up to 6 m as an option - ** - ISO grade 80

