



- YOKE Swivels are manufactured using the highest grade of material available.
- YOKE Swivels are designed with a safety factor of 5:1.
- YOKE Swivels are available in sizes from 3/4 Tons to 35 Tons.
- YOKE Swivels are available for wire lines 1/4" to 1-1/2".
- YOKE Swivels are zinc plated for corrosion resistance and longer life.
- YOKE Swivels are manufactured with grease fittings for superior performance.
- YOKE Swivels are designed for low starting torque and high rotation speed.
- All Swivels parts are 100% magnaflux crack detected.
- 20,000 cycle fatigue rate to 1.5 times working load limit.
- All parts with batch number for quality certified and traceability.

Angular Contact Bearing Swivels - Jaw + Jaw

Item No.	Wire Line Size	Working Load Limit Tons*	Dimensions (inch)								N.W. lbs
	inch		A	B	C	D	G	H	K	L	
8-303-0075	1/4	0.75	0.60	1.30	0.50	0.40	0.20	0.90	4.10	5.00	1.1
8-303-015	3/8	1.5	0.70	1.60	0.80	0.50	0.30	1.00	4.40	6.00	2.0
8-303-03	1/2	3	0.90	2.00	1.00	0.80	0.40	1.30	6.20	8.20	5.1
8-303-05	5/8	5	1.30	2.50	1.20	0.90	0.60	1.50	8.00	10.30	9.7
8-303-085	3/4	8.5	1.60	3.00	1.30	1.20	0.60	2.10	10.00	12.60	16.8
8-303-10	7/8	10	1.70	4.00	1.90	1.50	1.00	2.10	12.40	16.20	43.0
8-303-15	1	15	1.90	4.30	2.00	1.50	1.00	2.20	12.40	16.50	47.8
8-303-25	1 1/4	25	2.40	5.20	2.60	2.00	1.20	2.80	14.70	20.00	87.0
8-303-35	1 1/2	35	2.40	5.20	2.60	2.00	1.20	2.80	14.70	20.00	87.0

★ Minimum Ultimate Load is 5 times the Working Load Limit.
 Maximun Proof Load is 2 times the Working Load Limit.

Item No.	Wire Line Size	Working Load Limit Tons*	Dimensions (mm)								N.W. kg
	mm		A	B	C	D	G	H	K	L	
8-303-0075	6	0.75	15	32	13	10	6	22	103	128	0.5
8-303-015	10	1.5	18	40	20	13	8	26	112	152	0.9
8-303-03	13	3	23	51	25	19	10	32	158	208	2.3
8-303-05	16	5	32	64	31	22	14	37	200	261	4.4
8-303-085	19	8.5	40	76	34	30	14	54	252	320	7.6
8-303-10	22	10	42	102	48	38	25	54	316	412	19.5
8-303-15	25	15	48	108	52	38	25	57	316	420	21.7
8-303-25	32	25	62	132	65	51	30	70	374	503	39.5
8-303-35	38	35	62	132	65	51	30	70	374	503	39.5

★ Minimum Ultimate Load is 5 times the Working Load Limit.
 Maximun Proof Load is 2 times the Working Load Limit.