



- YOKE Swivels are manufactured using the highest grade of material available.
- YOKE Swivels are designed with a safety factor of 5:1.
- YOKE Swivels are available in sizes from 3/4 Tons to 35 Tons.
- YOKE Swivels are available for wire lines 1/4" to 1-1/2".
- YOKE Swivels are zinc plated for corrosion resistance and longer life.
- YOKE Swivels are manufactured with grease fittings for superior performance.
- YOKE Swivels are designed for low starting torque and high rotation speed.
- All Swivels parts are 100% magnaflux crack detected.
- 20,000 cycle fatigue rate to 1.5 times working load limit.
- All parts with batch number for quality certified and traceability.

Angular Contact Bearing Swivels - Eye + Jaw

Item No.	Wire Line Size	Working Load Limit Tons*	Dimensions (inch)											N.W. lbs
	inch		A	B	D	G	H	I	J	K	L	T	W	
8-305-0075	1/4	0.75	0.60	1.30	0.40	0.20	0.90	0.70	0.80	4.06	5.28	0.50	1.50	1.1
8-305-015	3/8	1.5	0.70	1.60	0.50	0.30	1.00	0.90	0.90	4.53	6.14	0.60	1.70	2.0
8-305-03	1/2	3	0.90	2.00	0.80	0.40	1.30	1.10	1.10	6.22	8.31	0.80	2.00	4.8
8-305-05	5/8	5	1.30	2.50	0.90	0.60	1.50	1.30	1.30	8.07	10.60	1.00	2.30	9.7
8-305-085	3/4	8.5	1.60	3.00	1.20	0.60	2.10	1.50	1.50	9.84	12.68	1.30	3.20	16.4
8-305-10	7/8	10	1.70	4.00	1.50	1.00	2.10	2.00	1.70	12.28	16.22	1.70	3.50	39.6
8-305-15	1	15	1.90	4.30	1.50	1.00	2.20	2.50	2.10	12.50	17.10	1.90	4.30	46.7
8-305-25	1 1/4	25	2.40	5.20	2.00	1.20	2.80	2.80	2.60	15.35	20.63	2.40	5.10	88.0
8-305-35	1 1/2	35	2.40	5.20	2.00	1.20	2.80	2.80	2.60	15.35	20.63	2.40	5.10	88.0

★ Minimum Ultimate Load is 5 times the Working Load Limit.
 Maximum Proof Load is 2 times the Working Load Limit.

Item No.	Wire Line Size	Working Load Limit Tons*	Dimensions (mm)											N.W. kg
	mm		A	B	D	G	H	I	J	K	L	T	W	
8-305-0075	6	0.75	15	32	10	6	22	18	19	103	134	12	37	0.5
8-305-015	10	1.5	18	40	13	7	26	22	23	115	156	15	43	0.9
8-305-03	13	3	23	51	19	10	32	28	27	158	211	20	51	2.2
8-305-05	16	5	32	64	22	14	37	33	33	204	268	26	59	4.4
8-305-085	19	8.5	40	76	30	14	54	38	37	250	322	32	82	7.4
8-305-10	22	10	42	102	38	25	54	52	44	313	413	42	90	18.0
8-305-15	25	15	48	108	38	25	57	64	54	314	430	49	110	21.2
8-305-25	32	25	62	132	51	30	70	70	66	391	526	60	130	40.0
8-305-35	38	35	62	132	51	30	70	70	66	391	526	60	130	40.0

★ Minimum Ultimate Load is 5 times the Working Load Limit.
 Maximum Proof Load is 2 times the Working Load Limit.