



- YOKE Swivels are manufactured using the highest grade of material available.
- YOKE Swivels are designed with a safety factor of 5:1.
- YOKE Swivels are available in sizes from 3/4 Tons to 35 Tons.
- YOKE Swivels are available for wire lines 1/4" to 1-1/4".
- YOKE Swivels are zinc plated for corrosion resistance and longer life.
- YOKE Swivels are manufactured with grease fittings for superior performance.
- YOKE Swivels are designed for low starting torque and high rotation speed.
- All Swivels parts are 100% magnaflux crack detected.
- 20,000 cycle fatigue rate to 1.5 times working load limit.
- All parts with batch number for quality certified and traceability.

## Angular Contact Bearing Swivels - Eye + Hook

Item No.	Wire Line Size	Working Load Limit Tons*	Dimensions (inch)								N.W. lbs
	inch		B	G	I	K	P	R	T	W	
8-307-0075	1/4	0.75	1.30	3.15	0.71	6.20	1.00	0.83	0.39	1.57	1.5
8-307-015	3/8	1.5	1.60	4.02	0.87	7.30	1.20	1.14	0.59	1.92	3.1
8-307-03	1/2	3	2.00	5.13	1.06	9.60	1.40	1.42	0.87	2.09	7.0
8-307-05	5/8	5	2.50	6.54	1.29	12.44	1.70	1.85	1.02	2.76	14.3
8-307-085	3/4	8.5	3.00	8.69	1.46	15.00	2.40	2.60	1.26	3.43	29.3
8-307-10	7/8	10	4.00	10.91	3.19	18.38	3.20	3.00	1.65	4.17	57.0
8-307-15	1	15	4.30	10.91	3.19	19.10	3.20	3.00	1.93	4.88	63.6
8-307-25	1 1/4	25	5.20	13.89	3.27	22.95	3.30	3.62	2.32	5.71	119.9

★ Minimum Ultimate Load is 5 times the Working Load Limit.  
 Maximum Proof Load is 2 times the Working Load Limit.

Item No.	Wire Line Size	Working Load Limit Tons*	Dimensions (mm)								N.W. kg
	mm		B	G	I	K	P	R	T	W	
8-307-0075	6	0.75	32	80	18	157	25	21	10	40	0.7
8-307-015	10	1.5	40	102	22	185	30	29	15	48	1.4
8-307-03	13	3	51	130	27	243	36	36	22	53	3.2
8-307-05	16	5	64	166	33	316	43	47	26	70	6.5
8-307-085	19	8.5	76	221	37	381	62	66	32	87	13.3
8-307-10	22	10	102	277	44	467	81	76	42	106	25.9
8-307-15	25	15	108	277	54	485	81	76	49	124	28.9
8-307-25	32	25	132	353	66	583	83	92	59	145	54.5

★ Minimum Ultimate Load is 5 times the Working Load Limit.  
 Maximum Proof Load is 2 times the Working Load Limit.