



- YOKE Swivels are manufactured using the highest grade of material available.
- YOKE Swivels are designed with a safety factor of 5:1.
- YOKE Swivels are available in sizes from 3/4 Tons to 35 Tons.
- YOKE Swivels are available for wire lines 1/4" to 1-1/4".
- YOKE Swivels are zinc plated for corrosion resistance and longer life.
- YOKE Swivels are manufactured with grease fittings for superior performance.
- YOKE Swivels are designed for low starting torque and high rotation speed.
- All Swivels parts are 100% magnaflux crack detected.
- 20,000 cycle fatigue rate to 1.5 times working load limit.
- All parts with batch number for quality certified and traceability.

Angular Contact Bearing Swivels - Jaw + Hook

Item No.	Wire Line Size	Working Load Limit Tons*	Dimensions (inch)									N.W. lbs
	inch		A	B	C	D	G	H	K	P	R	
8-308-0075	1/4	0.75	0.40	1.30	0.50	0.40	3.15	0.90	5.48	1.00	0.83	1.5
8-308-015	3/8	1.5	0.50	1.60	0.80	0.50	4.02	1.00	6.33	1.20	1.14	3.3
8-308-03	1/2	3	0.75	2.00	0.91	0.75	5.13	1.30	8.66	1.40	1.42	7.3
8-308-05	5/8	5	0.87	2.50	1.20	0.87	6.54	1.50	10.99	1.70	1.85	14.1
8-308-085	3/4	8.5	1.18	3.00	1.37	1.18	8.69	1.97	13.58	2.40	2.60	29.5
8-308-10	7/8	10	1.50	4.00	1.89	1.50	10.91	2.10	16.49	3.20	3.00	60.0
8-308-15	1	15	1.50	4.30	2.02	1.50	10.91	2.20	16.57	3.20	3.00	63.7
8-308-25	1 1/4	25	2.00	5.20	2.56	2.00	13.89	2.74	19.53	3.30	3.62	124.5

★ Minimum Ultimate Load is 5 times the Working Load Limit.
 Maximum Proof Load is 2 times the Working Load Limit.

Item No.	Wire Line Size	Working Load Limit Tons*	Dimensions (mm)									N.W. kg
	mm		A	B	C	D	G	H	K	P	R	
8-308-0075	6	0.75	15	32	13	10	80	22	139	25	21	0.7
8-308-015	10	1.5	18	40	20	13	102	26	161	30	29	1.5
8-308-03	13	3	23	51	23	19	130	32	220	36	36	3.3
8-308-05	16	5	32	64	31	22	166	37	279	43	47	6.4
8-308-085	19	8.5	37	76	35	30	221	50	335	62	66	13.4
8-308-10	22	10	42	102	48	38	277	54	419	81	76	27.2
8-308-15	25	15	48	108	52	38	277	56	421	81	76	28.9
8-308-25	32	25	62	132	65	51	353	69	496	83	92	56.6

★ Minimum Ultimate Load is 5 times the Working Load Limit.
 Maximum Proof Load is 2 times the Working Load Limit.